



## SMD CRYSTAL UNITS

## 1.6\*1.2 Seam Sealing Crystal

- . Very compact and thin(1.6\*1.2\*0.4mm MAX)
- . Frequency range of 24M-54M with Found
- . lead-free meets the requirements for re-flow profiling using lead-free solder

1	Nominal Frequency 标称频率	24~54MHz
2	Hold ing 封装形式	SMD 1612
3	Vibration Mde 振动模式	AT CUT, FUND. AT 切, 基波
4	Frequency Tolerance @ 25±3°C 调整频差	±10PPM / ±20PPM/ ±30PPM
5	Frequency Stability@ 6 工作温度条件下的频率容差	±10PPM / ±20PPM/ ±30PPM
6	Operating Temperature Range 工作温度	-20~+70°C / -40~85°C
7	Store Temperature Range 存储温度	-55~+125°C
8	Equivalency Resistance 等效电阻	60~100 Ω max
9	Load Capacitance 负载电容	8~30PF
10	Drive Level 激励功率	100 μ W max
11	Insulation Resistance 绝缘阻抗	>500MΩ at DC 100V±15V
12	Aging 老化	±3PPM/year max



HUBEI JINGMAO ELECTRONICS CO., LTD.

湖北晶茂电子科技有限公司

# CRYSTAL CERAMIC SMD 1.6\*1.2 4PAD DIMENSION

PACKAGE DIMENSIONS:Unit: mm

